



## Solid State Devices, Inc.

14701 Firestone Blvd \* La Mirada, Ca 90638  
 Phone: (562) 404-4474 \* Fax: (562) 404-1773  
 ssdi@ssdi-power.com \* www.ssdi-power.com

### SUM60F thru SUM100F and SUM60FSMS thru SUM100FSMS

**500 mA**  
**FAST RECOVERY RECTIFIER**  
**6,000 thru 10,000 VOLTS**  
**180 nsec**

## Designer's Data Sheet

### Part Number/Ordering Information <sup>1/</sup>

SUM

— — —

#### L Screening <sup>2/</sup>

— = Not Screened

TX = TX Level

TXV = TXV Level

S = S Level

#### Package Type

— = Axial Leaded

SMS = Surface Mount Square Tab

#### Voltage/Family

60F = 6,000V

70F = 7,000V

80F = 8,000V

90F = 9,000V

100F = 10,000V

### FEATURES:

- PIV to 10,000 Volts
- Hermetically sealed axial and square tab surface mount package
- Fast recovery 180 nsec maximum <sup>4/</sup>
- Void free construction
- Metallurgically bonded
- 175°C maximum operating temperature
- TX, TXV, and S-level screening available <sup>2/</sup>
- Also available in fast versions, consult factory

### MAXIMUM RATINGS <sup>3/</sup> <sup>6/</sup>

RATING			SYMBOL	VALUE	UNIT
Peak Inverse Voltage			PIV	6000	Volts
				7000	
				8000	
				9000	
				10000	
Average Rectified Current	Axial @ L = 3/8"	Surface Mount	I <sub>O1</sub> I <sub>O2</sub>	500	mA
	T <sub>L</sub> ≤ 90°C	T <sub>EC</sub> ≤ 130°C		250	
	T <sub>L</sub> ≤ 125°C	T <sub>EC</sub> ≤ 145°C			
Surge Current (1 Cycle)			I <sub>FSM</sub>	30	Amps
Operating & Storage Temperature <sup>5/</sup>			T <sub>J</sub> and T <sub>STG</sub>	-65 to +175	°C
Typical Thermal Impedance	Junction to Lead for Axial, L = .375"		R <sub>θJL</sub>	15	°C/W
	Junction to End Tab for Surface Mount		R <sub>θJE</sub>	5	

### NOTES:

<sup>1/</sup> For ordering information, price, operating curves, and availability- contact factory.

<sup>2/</sup> Screening based on MIL-PRF-19500. Screening flows available on request.


<sup>3/</sup> Unless otherwise specified, all electrical characteristics @25°C.

<sup>4/</sup> I<sub>F</sub> = 500mA, I<sub>R</sub> = 1A, I<sub>RR</sub> = 250mA, T<sub>A</sub> = 25°C


<sup>5/</sup> Maximum lead/end temperature for soldering is 250°C, 3/8" from the case for 5 sec. maximum.

<sup>6/</sup> Operating and testing over 10,000 V/inch may require encapsulation or immersion in suitable dielectric material.

Axial Leaded



SMS



**NOTE:** All specifications are subject to change without notification.  
 SCD's for these devices should be reviewed by SSDI prior to release.

**DATA SHEET #: RC0037E**

**DOC**



**Solid State Devices, Inc.**

14701 Firestone Blvd \* La Mirada, Ca 90638

Phone: (562) 404-4474 \* Fax: (562) 404-1773

ssdi@ssdi-power.com \* www.ssdi-power.com

**SUM60F thru SUM100F  
and  
SUM60FSMS thru SUM100FSMS**

**ELECTRICAL CHARACTERISTICS <sup>3/ 6/</sup>**

CHARACTERISTICS		SYMBOL	VALUE	UNIT
Maximum Forward Voltage (pulsed)	$I_F = 500 \text{ mA}$	$V_F$	13.5	Vdc
Maximum Reverse Leakage Current ( $V_R = \text{Rated}$ )	( $T_A = +25^\circ\text{C}$ ) ( $T_A = +100^\circ\text{C}$ )	$I_{R1}$ $I_{R2}$	1.0 15	$\mu\text{A}$ $\mu\text{A}$
Maximum Junction Capacitance $V_R = 100 \text{ Vdc}$ , $f = 1\text{MHz}$ , $T_A = 25^\circ\text{C}$		$C_J$	8	pF
Maximum Reverse Recovery Time $I_F = 500\text{mA}$ , $I_R = 1\text{A}$ , $I_{RR} = 250\text{mA}$ , $T_A = 25^\circ\text{C}$		$t_{rr}$	180	ns

**Package Outlines:**

DIMENSIONS (inches)			DIMENSIONS (inches)		
DIM.	Minimum	Maximum	DIM.	Minimum	Maximum
A	.115	.165	A	.170	.180
B	---	.310	B	.330	.380
C	.047	.053	C	.020	.030
D	1.00	---	D	.002	---

<p><b>AXIAL</b></p>	<p><b>SMS</b></p>
---------------------	-------------------

**NOTE:** All specifications are subject to change without notification.  
SCD's for these devices should be reviewed by SSDI prior to release.

**DATA SHEET #: RC0037E**

**DOC**